ITEM	MODIFICATION	DATE	DRAW	APPROVE
A0	新版发行	2020-11-01	望 盛	袁俊林















PCB LAYOUT 图仅供参考

Note:
1.Material:
1.1 Housing:High temperature thermoplastic UL94V-0
1.2 Contact:Copper Alloy
1.3 Shell:Metal Alloy.
1.4 Middle plate:SUS
2.ELECTRICAL:
2-1:CURUENT RATAING:
VBUS AND GND CONTACTS RATED AT 3A Max
VBUS AND GND CONTACTS RATED AT 0.5A Min
0.9Amps Max.for all other contact.
PARALLELED FOR A TOTAL OF 5A;
2-2:INITIAL CONTACT RESISTANCE:40 MILLIOHMS
2-3:DIEELECTRIC WITHSTANDING VOLTAGE:100V AC MIN;
3:MECHANICAL CHARACTERISTICS:
3-1:MATING FORCE:5~20N
3-2:UNMATING FORCE:8~20N(INITIAL),6~20N(AFTER 10000 CYCLES)
3-3:FREQUENCE:200±50 CYCLES/HOUR,10000 CYCLES
3-4:OPERATING TEMPERATURE;-40°~80°.
4:WATERPROOF:IP-X8.
CX003

4	HOUSING	LCP BLACK
3	RING	RED Silica Gel
2	Shell	Zinc Alloy Ni80u"
1	Contact	C5191 半金雾锡3U+1"
ITEM	DEFINITION	SPEC DESCRIPTION

TABLE B

A5	CC1	B12	GND
A9	VBUS	B9	VBUS
A12	GND	B5	CC2
PIN	SIGNAL NAME	PIN	SIGNAL NAME

TOLERANCE UNLESS OTHERWISE SPECIFIED

.X±0.15	Ang.±1°
.XX±0.10	
.XXX±0.05	

PROJ.

DIMENSION STYLE
MM ONLY

DESIGN UNITY
METRIC

SCALE
1:1

CXUN® 东莞市超讯电子有限公司
transcend communication

DRAWN BY 望 盛	DATE 2020-11-01	TITLE TYPE C 6PIN SMT 防水有钢片	
CHECKED BY 望 盛	DATE 2020-11-01	PART NO. BNF01S2203R-W	SHEET NO. 1 OF 1
APPROVED BY 袁俊林	DATE 2020-11-01	MOLD NO. DWG-USB CF-064	C REV. A0